1/2



MANHOLE ACCESS COVERS

MANHOLE COVER - LOCKED HINGED LIFT ASSISTED **ARES CLASS D400**











PLACE OF INSTALLATION:

D400 Middle Traffic (T3) _ Speed limit (50Km/h. max)

SPECIFICATIONS:

Norm: EN 124-2 Loading: 400 kN Quality Label : Tüv (w)

MATERIAL & COATING:

Cover & Frame: Spheroidal Cast Iron EN-GJS-500-7. Water Based Black Paint Hardware: Stainless Steel / Cast Iron

Gasket: EPDM monobloc


OPTIONS:

Custom Badging & Logo Special lock: burglar-proof SAE Standard lock: 1/4 turn

REMARKS:

Lift assisted by stainless steel mechanical springs. Selflocking by means of ductile iron spring bar «Pushed -Slammed».

Safety blocking to prevent accidental cover closure, activated automatically at the opening of the cover. Handling: Opening and handling of the cover without specific tools.





Ref.	Description	lay-out	Clear opening	A *	В*	H*	Total weight
			mm				Kg
38154	ARES		900 x 900	1130	980	102	224

^{*}External frame measuress



MANHOLE ACCESS COVERS

2/2 | MANHOLE COVER - LOCKED HINGED LIFT ASSISTED ARES CLASS D400



CABLE-PASS

2 dedicated **cable-pass areas** are pre-equipped on the ARES cover and can be quickly opened **(breakable plates in cast iron).**





IDENTIFICATION FINITION & CUSTOMIZATION

On request:

- -1 badging area for customization of 450 x 250 mm by **casting on the cover** or with an insert plate made of powder-coated cast iron (color of your choice).
- 2 badging areas are available for customization of 180 x 40 mm with stainless steel plates.

SAFETY BLOCKING DEVICE



At the opening, **safety blocking device** (gravity pawl) automatically locks the cover and prevents the cover from being accidentally closed.

A locking pin in option adds an extra level of safety.



Easy closing & **effortless** by only rising the device.

Selflocking by means of ductile iron spring bar «Pushed - Slammed»

Associated products

